

WHITE PVC CARDS

Quality and Reliability



Evolis PVC cards are the ideal support for outstanding printouts. Their even and flat surface ensures flawless moves under the print head (minimizing the risk of damage) and printouts with vivid colors and well-defined barcodes.

ADVANTAGES

The quality of our cards allows an optimal printing quality and a good readability for specific elements (texts, barcodes, etc.).

Additionally, as the cards are in PVC, they are flexible but very resistant and solid.

Tested and validated by Evolis R&D and Quality departments, these consumables bring you printing quality and reliability.

GENERAL SPECIFICATIONS

- Cards in PVC – Blank white – Mirror finish
- Compliant with ISO CR-80 (ISO 7810) standards
- Dimension: 85.6 mm x 54 mm (3 3/8" x 2 1/8")
- Available in two thicknesses:
 - 0.76 mm / 30 MIL (Part Number C4001 and CBG0030W)
 - 0.50 mm / 20 MIL (Part Number C4002 and CBG0020W)
- Cards lifespan: up to 3 years (minimum lifespan based on a credit card usage, high frequency)



PRODUCT INFORMATION:

- PVC Cards
- Blank White
- 20 MIL and 30 MIL



COMPATIBILITY AND CAPACITY

PART#	PACKAGE	ZENIUS/ PRIMACY	PRIMACY2	PRIMACY LAMINATION	AGILIA	AVANSIA/ AVANSIA LAMINATION	QUANTUM	EDIKIO ACCESS EDIKIO FLEX EDIKIO DUPLEX
C4001	5 boxes of 100 cards	•	•	•	•	•	•	•
C4002	5 boxes of 100 cards	•	•					

PART#	PACKAGE	BADGY
CBG0030W	1 box of 100 cards	•
CBG0020W	1 box of 100 cards	•

STORAGE INFORMATION

The cards shall be capable of functioning for up to 2 years after purchase if stored in a cool, dry environment and having remained unopened from the original packaging. Temperature of storage must be between 15-30°C (59-86°F) and at RH between 10-60%. Once opened, avoid dust, direct sunlight, high humidity and high temperatures. Do not place near solvent or other chemicals.

INSTRUCTIONS FOR USE

In order to optimize the printing quality and card durability:

- Do not use cards that have been damaged, folded or dropped on the floor.
- Do not touch the printable surface of the cards in order to preserve print quality.
- Do not use in high temperature conditions. Do not place near heat sources or open flames (degradation above 60°C/140°F). Avoid thermal shock.
- Avoid dishwasher and chemicals, wash your printed cards using clean cold water.



Evolis - 14 avenue de la Fontaine - Z.I. Angers-Beaucouzé 49070 Beaucouzé - France
T +33 (0) 241 367 606 - F +33 (0) 241 367 612 - info@evolis.com

www.evolis.com